



MNT BEARING LTD

HSR45HA[1,2,3,4,5,6,7,8,9]+ [188-3000/1]L THK Standard Linear Guide Accuracy and Preload Selectable HSR Series

Bearing No.
HSR45HA[1,2,3,4,5,6,7,8,9]+[188-3000/1]L

HSR45HA[1,2,3,4,5,6,7,8,9]+[188-3000/1]L Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Block Type	[Wide Long] HA: Long Flanged w/Tapped Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	45
Rail Width W1	45 mm
Material	Carbon Steel
Mounting Height M	60 mm
Rail Length L	188 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Retainer	Available
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	100000
Basic Load Rating Static Rating Co(N)	135000
Allowable Static Moment MA(N m)	2590
Allowable Static Moment MB(N m)	2590
Allowable Static Moment MC(N m)	2600
Block external dimension	120 mm



MNT BEARING LTD

W	
Block external dimension L	170.8 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension S(M)	M12
Mounting Hole Screw Depth	Through mm
Block dimension L1	129.8 mm