



MNT BEARING LTD

5SRS7N[SS,UU]C1+[33-300/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 5SRS7N[SS,UU]C1+[33-300/1]L[H,P]M

Days to Ship	27 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	5
Nominal Part Number	7
Rail Type	Standard
Rail Width W1	7 mm
Mounting Height M	8 mm
Rail Length L	33 ~ 300 mm
Radial Clearance	Light Preload
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2010
Basic Load Rating Static Rating Co(N)	2310
Allowable Static Moment MA(N m)	7.77
Allowable Static Moment MB(N m)	8.96
Allowable Static Moment MC(N m)	8.96
Symbols for Dust Resistance	SS: End and Side Seals / UU: End Seals (Best Leadtime)
Block external dimension W	17 mm

5SRS7N[SS,UU]C1+[33-300/1]L[H,P]M Bearing
2D drawings and 3D CAD models



MNT BEARING LTD

Block external dimension L	31 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M2
Mounting Hole Screw Depth	2.3 mm
Block dimension L1	21 mm